


Technical drawing of a mechanical assembly, likely a bridge or a large frame, showing dimensions in millimeters. The drawing includes a central vertical structure and two horizontal arms extending from it. Key dimensions are labeled:

- Overall width: 8100
- Overall height: 3500
- Horizontal arm length (left): 3200
- Horizontal arm length (right): 3200
- Vertical distance between horizontal arms: 3000
- Distance from central vertical structure to the end of the horizontal arms: 1700
- Distance from the end of the horizontal arms to the central vertical structure: 1950
- Distance from the end of the horizontal arms to the central vertical structure (top view): 3080
- Distance from the end of the horizontal arms to the central vertical structure (bottom view): 3080
- Distance from the end of the horizontal arms to the central vertical structure (diagonal view): 4330
- Distance from the end of the horizontal arms to the central vertical structure (diagonal view): 4470
- Distance from the end of the horizontal arms to the central vertical structure (diagonal view): 3090
- Distance from the end of the horizontal arms to the central vertical structure (diagonal view): 8680
- Distance from the end of the horizontal arms to the central vertical structure (diagonal view): 3080

## POVRCH TLUMÍCÍ PÁD - SYPKÝ MATERIÁL (kačírek, písek, mulčovací kůra) TL. 300 MM



Objem betonu min. 0,85 m<sup>3</sup>, beton C16/20.

## BETONÁŽ PROVÉST AŽ PO MONTÁŽI HERNÍHO PRVKU!

$\pm 0,000$  = finální úroveň dopadové plochy

- hranice dopadové plochy herního prvku  
**s nuceným pohybem** - **nesmí** se protínat  
s hranicí dopadové plochy jiného prvku
- minimální prostor pro instalaci herní sestavy
-  vytyčovací bod

Zhutnění zemní pláně na  $E_{def2}$  min. 25 MPa!!!

|                                                                                                           |                          |           |                                |                     |           |
|-----------------------------------------------------------------------------------------------------------|--------------------------|-----------|--------------------------------|---------------------|-----------|
| <br><b>hřiště.cz</b> |                          | Formát    | A3                             | Měřítko             | 1:40/1:20 |
|                                                                                                           |                          | Datum     | 12.01.2023                     |                     |           |
|                                                                                                           |                          | Vytvořila | Ing. Kateřina Vařejková        |                     |           |
|                                                                                                           |                          | Kontakt   | katerina@hriste.cz 797 971 007 |                     |           |
| Název                                                                                                     | RR EWAN<br>spodní stavba |           | Výška pádu                     | 1,5 m               |           |
| Číslo                                                                                                     | RR-0059-00               |           | Velikost dop. plochy           | 25,1 m <sup>2</sup> |           |
|                                                                                                           |                          |           | Povrch tlumící pád             | KAČÍREK/MULČ/PÍSEK  |           |