

Technical drawing of a mechanical assembly, likely a pump or motor, showing dimensions and labels. The drawing includes a top view and a side view.

Top View Dimensions:

- Overall width: 6270
- Overall height: 4150
- Horizontal segments: 1500, 2770, 2000
- Vertical segments: 1500, 1150, 1500
- Internal horizontal segments: 630, 1260, 630
- Internal vertical segments: 1150, 1700
- Radius dimensions: R1500 (multiple locations), R1500 (bottom right), R1500 (top right)
- Angle dimensions: 3050, 2120, 5450, 5000

Labels:

- A:** Two locations, likely indicating the center of the main circular components.
- B:** Four locations, likely indicating the center of the smaller circular components.
- C:** One location, likely indicating the center of the rectangular component.

Side View Dimensions:

- Overall width: 6270
- Overall height: 4150
- Horizontal segments: 1500, 2770, 2000
- Vertical segments: 1500, 1150, 1500
- Internal horizontal segments: 630, 1260, 630
- Internal vertical segments: 1150, 1700
- Radius dimensions: R1500 (multiple locations), R1500 (bottom right), R1500 (top right)
- Angle dimensions: 3050, 2120, 5450, 5000

POVRCH TLUMÍCÍ PÁD - TRÁVNÍK



A - 450x450 mm, hl. -0,7 m (2x)
B - 300x300 mm, hl. -0,7 m (4x)
C - 300x750 mm, hl. -0,7 m (1x)

Objem betonu min. 0,4 m³, beton C16/20.

BETONÁŽ PROVÉST AŽ PO MONTÁŽI HERNÍHO PRVKU!

$\pm 0,000$ = finální úroveň dopadové plochy

— — — hranice dopadové plochy herní sestavy

----- hranice dopadové plochy herního prvku
s nuceným pohybem - nesmí se protínat
s hranicí dopadové plochy jiného prvku



vytyčovací bod

Zhutnění zemní pláň na E_{def2} min. 25 MPa!!!

	Formát	A3	Měřítko	1:40/1:20
	Datum	10.01.2023		
	Vytvořila	Ing. Kateřina Vařejková		
	Kontakt	katerina@hriste.cz	797 971 007	
Název	RR ALROY spodní stavba		Výška pádu	0,95 m
Číslo	RR-0139-00		Velikost dop. plochy	21,0 m ²
			Povrch tlumící pád	TRÁVNÍK